

Project : Type : Part#:

WALL-MOUNTED AC CHARGING PILE



Features

Wall-mounted AC charging pile is mainly used for AC slow charging of electric vehicles.

The product integrates charging control and guidance, human-computer interaction control, communication, billing and metering, and other functions.

It has good dust-proof and waterproof functions, and the protection level reaches 4.

It can work safely indoors and outdoors (with a rain-proof shed).

Application: Residential charging and Commercial charging. Instructions: Start by swiping a card or entering password, which is convenient and quick, and can be operated by a mobile phone after networking.

Passed ETL and FCC, ENERGY STAR cerification applicable to the United States and Canada.

LOGO, color, function etc. are customizable.

OEM/ODM including size, shape etc. are available.



Power Coefficient			
Product Power	6KW-11.5KW optional		
Input Voltage	120-250VAC		
Input Frequency	47~63HZ		
Maximum Output Current	32A, 40A, 48A		
Input line Number	Three Lines -L1, N, earth wire		
Man-Machine Interaction and Startu	p Method		
Charging Method	Standard: Offline card swiping, Password charging, Plug and charge		
	Optional: Online card swiping, Online APP code scanning		
Optional Communication Method	Ethernet, WIFI, Bluetooth, 4G		
Indicator Light	Two-color indicator light, Standby: green light always on; Charging: the green light flashes; Fault: the red light always on		
Display screen	4.3-inch touch screen		
Working Environment			
Storage Temperature	-30~70°C (-22°F~158°F)		
Working Temperature	-25~55°C (-13 °F~131°F)		
Relative Humidity	≤95%		
Protection Level	4		
Altitude	≤2000m		
Operational Environment	Outdoor (with canopy), indoor		
Usage Occasion	Residential and commercial charging		

256-801-9825



Defencive Function				
Leakage Protection	Yes, CCID20	Low-Voltage Protection	Yes	
Ground Protection	Yes	Overcurrent Protection	Yes	
Overvoltage Protection	Yes	Abnormal Protection of Charging Gun Wire Connection	Yes	
Man-Machine Interaction and Startup Method				
Installation Method	Wall-mounted			
	Floor-standing (optional)			
Number of Interfaces	1 (line length 5m), customizable charging gun line ≤ 7.5m			
Size	15.02″X9.50″X4.13″(381.4mmX241.4mmX105mm)			
Product Weight	7KG			
Housing Material	PC and ABS mixed material			
Customization Requirement				
Custom LOGO	Yes			
Customized Appearance	Yes			
Custom Specification	Yes			